



M22HT SUB-COMPACT TRACTOR SERIES





MODEL	M22HTLM	M22HTLB	M22HTLBM
Engine – YANMAR T4F	3 - Cylinder, 22 HP	3 - Cylinder, 22 HP	3 - Cylinder, 22 HP
Transmission	2-Range HST, Forward/Reverse Foot Pedal Control with Auto Throttle		
Power Take-Off (PTO)	Hydraulic Independent 2-Speed: 540 Rear, 2500 Mid		
PTO Engagement	Independent, Electro – Hydraulic 2-Position Switch		
PTO HP	17.6	17.6	17.6
3-Point Hitch	CAT 1, Position Control, Turnbuckle/Chain Sway Adjustment		
3-Point Hitch Lift Capacity	1,100 Lbs. (499 kg)		
Hydraulic Total Flow	6.97 GPM (26.4 L)		
Power Steering Flow	2.11 GPM (8 L)		
Mid-Mount Mower	Shaft Drive 54" Cutting Width	-	Shaft Drive 54" Cutting Width
QA Front End Loader	Quick Attach with Dual Lift and Dual Bucket Cylinders, 48 inch Bucket		
Loader Max Lift Height	71.3 in (1810 mm)	71.3 in (1810 mm)	71.3 in (1810 mm)
Loader Max Lift Capacity	617 Lbs. (280 kg)	617 Lbs. (280 kg)	617 Lbs. (280 kg)
Backhoe	-	Full Subframe Quick Attach with 9 inch Bucket	
Backhoe Digging Depth	-	77 inch (1956 mm)	
R4 / Turf Tire Size	Front: 18 x 8.50 – 10 / Rear: 26 x 12.00 -12		
Complete Package Weight	2,060 Lbs. (934 kg)	2,585 Lbs. (1172 kg)	2,785 Lbs. (1263 kg)



FOLLOW US



www.facebook.com/ZetorNorthAmerica

www.twitter.com/ZetorNA

www.instagram.com/ZetorNA

www.youtube.com/TraktoryZetor

ZETOR NORTH AMERICA

5784 Mining Terrace
Jacksonville, FL, USA 32257

PH: 904-647-7169

Fax: 904-647-9346

www.ZetorNA.com

Sales@ZetorNA.com

Service@ZetorNA.com

EVERY EFFORT HAS BEEN MADE TO ENSURE THAT THE INFORMATION CONTAINED IN THIS PUBLICATION IS ACCURATE AND CURRENT. HOWEVER, INACCURACIES, ERRORS OR OMISSIONS MAY OCCUR AND DETAILS OF THE SPECIFICATIONS MAY BE CHANGED AT ANY TIME WITHOUT NOTICE. THEREFORE, ALL SPECIFICATIONS SHOULD BE CONFIRMED WITH YOUR ZETOR DEALER OR THE MANUFACTURE BEFORE ANY PURCHASE. THE IMAGES/PHOTOS ARE FOR ILLUSTRATIVE PURPOSE AND MAY VARY FROM ACTUAL PRODUCTS. SUBJECT TO CHANGE. 01/2020