

Zetor

M-SERIES PRODUCT GUIDE



ZETOR 22HP to 82HP



22HP Sub Compact Series

MODEL	M22HTL	M22HTLB	M22HTLM	M22HTLBM
Engine	T4F, Yanmar, 3-Cylinder			
Engine HP	22 (16.4 kw)			
Transmission	2-Range HST with Auto Throttle, Forward/Reverse Foot Pedals Control			
Power Take-Off (PTO)	Hydraulic Independent 2-Speed: 540 Rear, 2500 Mid			
PTO Engagement	Independent, Electric-over-Hydraulic			
PTO HP	17.6			
3-Point Hitch	HD CAT 1, with HD Turnbuckle/Chain Sway Adjustment, Position Control			
3-Point Hitch Lift Capacity	1,100 Lbs. (499 kg)			
Hydraulic Total Flow	6.97 GPM (26.4 L)			
Power Steering Flow	2.11 GPM (8 L)			
Mid-Mount Mower	-		Drive-over Shaft Drive 54" Cutting Width	
QA Front End Loader	Quick Attach with Dual Lift and Dual Bucket Cylinders, Pin-on 48 inch Bucket			
Loader Max Lift Height	71.3 in (1810 mm)			
Loader Max Lift Capacity	620 Lbs. (281 kg)			
Full Subframe Backhoe & 9" Bucket	-	Standard	-	Standard
Backhoe Digging Depth	-	77 inch (1956 mm)	-	77 inch (1956 mm)
R4 Industrial and R3 Turf Tire Size	Front: 18 x 8.50 – 10 / Rear: 26 x 12.00 -12			
Complete Package Weight	2,060 Lbs. (934 kg)	2,585 Lbs. (1172 kg)	2,260 (1025 kg)	2,785 Lbs. (1263 kg)





25HP Compact Series

MODEL	M25HTL	M25HTLB
Engine	T4F, Yanmar, 3-Cylinder	
Engine HP	25.3 (18.86 kw)	
Transmission	2-Range HST, Cruise Control and Auto Throttle, Dual Pedals FWD/REV	
Power Take-Off (PTO)	Hydraulic Independent 2-Speed: 540 Rear, 2500 Mid	
PTO Engagement	Independent, Electric-over-Hydraulic	
PTO HP	20.2 (15.1 kw)	
3-Point Hitch	HD CAT 1, with HD Turnbuckle/Chain Sway Adjustment, Position Control	
3-Point Hitch Lift Capacity	1,325 Lbs. (601 kg)	
Hydraulic Total Flow	6.95 GPM (26.31 L)	
Power Steering Flow	2.3 GPM (8.7 L)	
QA Front End Loader	Quick Attach with Dual Lift and Dual Bucket Cylinders	
Loader Bucket	53" Bucket, Skid Steer Carrier (Optional Pin-on)	
Loader Max Lift Height	77 in (1956 mm)	
Loader Max Lift Capacity	1,325 Lbs. (601 kg)	
Full Subframe Backhoe & 12" Bucket	-	Standard
Backhoe Digging Depth	-	78 inch (1981 mm)
R4 Tire Size	Front: 23 x 8.50 – 12 / Rear: 12 – 16.5 R4 Industrial	
R3 Turf Tire Size	Front: 23 x 8.50 – 12 / Rear: 29 x 12.50 – 16.5 R3 Turf	
Optional Equipment	60" Drive-over, Shaft Drive Mid-Mount Mower	
Optional Accessories	1-Rear Remote Valve and or Front End Loader 3rd Function	
Package Weight	2,400 Lbs. (1088 kg)	3,325 Lbs. (1508 kg)





39HP Compact Series

MODEL	M40HTC	M40SS
Engine	T4F, Yanmar (3 – Cylinder)	
Engine HP	39.2 (29.23 kw)	
Transmission	3 – Range HST, Dual Pedal FWD/REV	12 / 12 Synchro-Shuttle
Transmission Features	Electronic Cruise & Auto Throttle	Creeper, 2 - Speeds
PTO HP	31.3 (23.34 kw)	33.3 (24.8 kw)
Power Take-Off (PTO)	540 Rear / Optional 2000 Mid	540 Rear
PTO Type and Engagement	Independent, Electric–over–Hydraulic with Manual and Auto Control	
3-Point Hitch	HD CAT 1 with Extendable Link Ends and Telescopic Stabilizers	
3-Point Hitch Control	Position / Optional Draft	
3-Point Hitch Lift Capacity	2,650 Lbs. (1202 kg)	
Hydraulic Total Flow	12.0 GPM (45.4 L)	
Rear Valves	2 - Standard	
Mid Valves	2 - Standard with 4 – Couplers & Factory Joystick	
3rd Function Control	Optional	
Flow to Remotes and Loader	7.0 GPM (26.5 L)	
Power Steering Flow	4.6 GPM (17.6 L) with Tilt	
QA Front End Loader	Quick Attach with 66" Bucket, Skid Steer Carrier	
Loader Max Lift Height	103 in (2616 mm)	
Loader Max Lift Capacity	2,235 Lbs. (1014 kg)	
Front Tire Size	R4 Industrial 10 – 16.5 OR R1 AG 8 - 16	
Rear Tire Size	R4 Industrial 43 x 16.00 – 20 OR 12.4 – 24 Adjustable	
Operator Platform	All Weather Premium ISO CAB, Rubber Mat	ISO with Folding ROPS, Rubber Mat
Main Premium Accessories	Stereo, Tilt, 7-Pin Socket, Dome Light, Horn, Recline and Folding Seat, Armrest, Front/Rear CAB Lights and Wipers, Left/Right Doors and Mirrors	Tilt, 7-Pin Socket, Horn, Rear Work Light
Max Height inch (R4)	92.5	94.4 up / 66.5 down
Complete Package Weight	4,780 Lbs. (2168 kg)	4,430 Lbs. (2009 kg)

*Weights, Front Fenders, Front 3-Point Hitch, Pallet Forks, Air-Ride Seat, Optional





59HP Utility Compact Series

MODEL	M60SS	M60HTC
Engine	T4F, Yanmar, 4-Cylinder Turbocharged	
Engine Max HP	59 (44 kw)	
Transmission	16 / 16 Synchro Shuttle, Creeper	3-Range HST, Electronic Cruise, Load Sense, Auto Throttle
Power Take-Off (PTO)	Independent 540 Rear, (Optional 540E)	
PTO Engagement	Independent, Electric-over-Hydraulic with Manual and Auto Control	
PTO HP	50.2	47.2
CAT 1, 3-Point Hitch	Telescopic Stabilizers, Extendable Ball Ends, Sliding/Swinging Drawbar with Hammerstrap & Pin	
3-Point Hitch Control	Position / Draft / Mix	
3-Point Hitch Lift Capacity	3,314 Lbs. (1503 kg)	
Hydraulic Total Flow	15.5 GPM (58.7 L)	
Rear Valves	2 - Standard with 4 – Couplers, (Option – 3)	
Mid Valves	2 - Standard with 4 – Couplers & Factory Joystick	
3rd Function Control	Joystick Pre-wired 3rd Function / Hydraulic Kit Optional	
Flow to 3-PTH & Loader	10.5 GPM (37.85 L)	
Power Steering Flow	5.5 GPM (20.8 L) with Tilt	
QA Front End Loader	Quick Attach with 72" Bucket, Skid Steer Carrier	
Loader Max Lift Height	109.1 in (2771 mm)	
Loader Max Lift Capacity	2,500 Lbs. (1134 kg)	
Front Tire Size	12–16.5 R4 Industrial OR 280/70R18 R1W AG Radial Adjustable	
R4 Rear Tire Size	16.9–24 R4 Industrial OR 380/70R28 R1W AG Radial Adjustable	
Operator Platform	ISO Folding ROPS with Rubber Mat	All Weather Premium ISO CAB, Rubber Mat
Main Premium Accessories	Tilt, 7-Pin Socket, Horn, Rear Work Light, L/R Mirrors, External 3-Point Hitch Control	Stereo, Tilt, 7-Pin Socket, Dome Light, Horn, Recline and Folding Seat, Front/Rear CAB Lights and Wipers, Left/Right Doors and Mirrors, External 3-Point Hitch Control
Max Height (R4)	102.1 in up /	99.6 in (2530 mm)
Complete Package Weight	5,400 Lbs. (2449 kg)	5,800 Lbs. (2631 kg)

Options: Weights, Pallet Forks, Grapple, Air-Ride Seat





75HP Utility Ag Series

MODEL	M70PSC
Engine	T4F, Deutz, 4-Cylinder Turbocharged
Engine Max HP	75
Engine Net HP	68
Transmission	24 / 24 Power Shuttle, Creeper
Power Take Off (PTO)	Independent 540/540E/1000
Transmission and PTO Clutch	Dual Multi-Wet Clutch Pack
PTO Engagement	Independent, Electric-over-Hydraulic with Manual and Auto Control
PTO HP	62
CAT 2: 3-Point Hitch	HD Telescopic Stabilizers and Extendable Ball Ends, HD Swinging Drawbar with Hammer Strap & Pin
3-Point Hitch Control	Position / Mix / Draft / Mechanical Control
3-Point Hitch Lift Capacity	4,270 LBS (1937 kg)
Hydraulic Total Flow	16.1 GPM (61 L)
Rear Remote Valves	2 – Standard / 3 - Optional
Mid Valves	2 – Standard, Factory Joystick
3rd Function	Standard, Factory Installed
Total Hydraulic Flow	16.5 GPM (62.46 L)
Flow to Remotes and Loader	10.5 GPM (39.74 L)
Loader Max Lift Height @ Pivot Pins	125 in (3175 mm)
Loader Max Lift Capacity	3,125 Lbs. (1417 kg)
R1 AG Front Tires	340/65R20 (13.6R20) R1W RADIAL Adjustable
R1 AG Rear Tires	420/70R30 (16.9R30) R1W RADIAL Adjustable
R4 Industrial Front Tires	12.5/80-18 R4 Adjustable
R4 Industrial Rear Tires	18.4 – 26 R4 Adjustable
Platform	Premium Climate Control ISO CAB with Mat, Stereo, AC/Heater/Forced Air Defrost
Overall Height	100.2 in (2545 mm)
Package Weight	8,485 LBS (3848 KG)

**Weights, Front Fenders, Front 3-Point Hitch, Pallet Forks, Air-Ride Seat, Optional*





82HP Utility Ag Series

MODEL	M85SSC
Engine	T4F, Deutz, 4-Cylinder Turbocharged
Engine Max HP	82
Engine Net HP	75
Transmission	12 / 12 Synchronized Mechanical Shuttle
Power Take Off (PTO)	Independent 540/1000
Transmission and PTO Clutch	Dual 11" Dry Cerametallic Disc
PTO Engagement	Independent, Mechanical Lever/Cable Control
PTO HP	67
CAT 2: 3-Point Hitch	HD Telescopic Stabilizers and Extendable Ball Ends, HD Swinging Drawbar with Hammer Strap & Pin
3-Point Hitch Control	Position / Mix / Draft / Mechanical Control
3-Point Hitch Lift Capacity	5,500 LBS (2495 kg)
Hydraulic Total Flow	20 GPM (75.7 L)
Rear Remote Valves	2 – Standard / 3 - Optional
3rd Function	Standard, Factory Installed
Power Steering Flow	6.0 GPM (22.7 L)
Flow to Remotes and Loader	14 GPM (53 L)
Loader Max Lift Height @ Pivot Pins	157.4 in (4000 mm)
Loader Max Lift Capacity	2,900 Lbs. (1300 kg)
R1 AG Front Tires	12.4 - 24 R1 AG Adjustable
R1 AG Rear Tires	18.4 - 30 R1 AG Adjustable
R4 Industrial Front Tires	10.5/80-18 R4 Adjustable
R4 Industrial Rear Tires	18.4 – 24 R4 Adjustable
Platform	Climate Control ISO CAB with Mat, Stereo, AC/Heater/Forced Air Defrost
Overall Height	101.4 in (2575 mm)
Package Weight	9,925 LBS (4501 KG)

*Weights, Front Fenders, Front 3-Point Hitch, Pallet Forks Optional



Zetor



ZETOR NORTH AMERICA

5784 Mining Terrace
Jacksonville, FL, 32257
PH: 904-647-7169
Fax: 904-647-9346
www.zetorna.com
sales@zetorna.com
service@zetorna.com

FOLLOW US



www.facebook.com/ZetorNorthAmerica
www.twitter.com/ZetorNA
www.instagram.com/zetorna
www.youtube.com/TraktoryZetor

Every effort has been made to ensure that the information contained in this publication is accurate and current. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your ZETOR dealer or the manufacture before any purchase. The images/photos are for illustrative purpose and may vary from actual products. Subject to change. Rev 07/2021